

CHAIN PRODUCTS*


ONEPIECE™ LIVE TRANSFER




SERIES 900 Flush Grid • Center-driven • Open hinge • 1.07 in. (27.2 mm) pitch • Available widths: 4.7 in. (119.4 mm) and 6 in. (152.4 mm)



SERIES 900 Flat Top • Center-driven • Closed hinge • 1.07 in. (27.2 mm) pitch • Available widths: 4.7 in. (119.4 mm) and 6 in. (152.4 mm)




SERIES 1100 Flush Grid • Hinge driven • Open hinge • 0.6 in. (15.2 mm) pitch • Available width: 4 in. (76 mm) and up in 1 in. (25.4 mm) increments and 6 in. (152.4 mm) MTW




SERIES 1400 Flat Top • Center/hinge driven • Closed hinge • 1 in. (25.4 mm) pitch • Available widths: 6 in. (152.4 mm) and 9.3 in. (236.2 mm)

NOTE: Series 900 Live Transfer edges are also available with bricklaid belts. For more information, see the data pages in Section 2 or contact Intralox Customer Service.


MOLD TO WIDTH




SERIES 900 Flush Grid • Center-driven • Open hinge • 1.07 in. (27.2 mm) pitch • Available widths: 3.25 in. (82.6 mm), 4.5 in. (114.3 mm) and 7.5 in. (190.5 mm)




SERIES 900 Flat Top • Center-driven • Closed hinge • 1.07 in. (27.2 mm) pitch • Available widths: 3.25 in. (82.6 mm), 4.5 in. (114.3 mm) and 7.5 in. (190.5 mm)




SERIES 900 Flush Grid (85 mm) • Center-driven • Open hinge • 1.07 in. (27.2 mm) pitch • Available width: 85 mm




SERIES 900 Flat Top (85 mm) • Center-driven • Closed hinge • 1.07 in. (27.2 mm) pitch • Available width: 85 mm




SERIES 900 Raised Rib • Center driven • Closed hinge • 1.07 in. (27.2 mm) pitch • Available widths: 1.1 in. (29 mm), 1.5 in. (37 mm), 1.8 in. (46.5 mm) and 2.2 in. (55 mm)



SERIES 1400 Flat Top • Center/hinge driven • Closed hinge • 1 in. (25.4 mm) pitch • Available widths: 3.25 in. (83 mm), 4.5 in. (114 mm), 6.0 in. (125.4 mm) and 7.5 in. (191 mm)



SERIES 1400 Flat Top (85 mm) • Center/hinge driven • Closed hinge • 1 in. (25.4 mm) pitch • Available width: 85 mm



SERIES 4009 Flush Grid • Hinge driven • Closed hinge • 1 in. (25.4 mm) pitch • Available width: 83.8 mm (for parallel running at 85 mm)



SERIES 4009 Flat Top • Hinge driven • Closed hinge • 1 in. (25.4 mm) pitch • Available width: 83.8 mm (for parallel running at 85 mm)



SERIES 4014 Flat Top • Hinge driven • Closed hinge • 1 in. (25.4 mm) pitch • Available width: 83.8 mm (for parallel running at 85 mm)

* Intralox offers belt styles in dedicated width chains. These chain products come in industry standard widths, and are available in 10 foot (3.05 m) increments.

KNUCKLE CHAIN



SERIES 3000 • Center-driven •
Closed hinge • 2 in. (50.8 mm) pitch •
Turning and straight running.
Available width: 57 mm (excluding
tabs)